

4 TAKTNI VANBRODSKI MOTORI EFI

	Model	Broj cilindara	Obujam (ccm)	Napajanje gorivom	Snaga (kw)	Težina (kg)	Rezervoar (L)	Pokretanje	Power Trim&Tilt	Ručica	Daljinska komanda bočna	Punjenje baterije (DC)	Digitalna elektronska komanda Drive by wire	LAN Tahometar	LAN Speed&fuel metar	Multi f. LCD 6YC 4.3"	Propeler	MPC kn	MPC gotovna kn
novo	F20GMHS	2	432	EFI	14,7	57	25	M		✓		opc.					Alu	27.105	25.750
novo	F20GMHL	2	432	EFI	14,7	59	25	M		✓		opc.					Alu	27.421	26.050
novo	F20GWHS	2	432	EFI	14,7	60	25	M/E		✓		✓					Alu	29.526	28.050
novo	F20GWHL	2	432	EFI	14,7	62	25	M/E		✓		✓					Alu	29.842	28.350
novo	F20GES	2	432	EFI	14,7	56	25	E			✓	✓		opc.			Alu	31.158	29.600
novo	F20GEL	2	432	EFI	14,7	58	25	E			✓	✓		opc.			Alu	31.474	29.900
novo	F20GEPS	2	432	EFI	14,7	61	25	E	✓		✓	✓		opc.			Alu	34.368	32.650
novo	F20GEPL	2	432	EFI	14,7	63	25	E	✓		✓	✓		opc.			Alu	34.684	32.950
	F25GMHS	2	432	EFI	18,4	57	25	M		✓		opc.					Alu	31.158	29.600
	F25GMHL	2	432	EFI	18,4	59	25	M		✓		opc.					Alu	31.474	29.900
	F25GWHS	2	432	EFI	18,4	60	25	M/E		✓		✓					Alu	33.579	31.900
	F25GWHL	2	432	EFI	18,4	62	25	M/E		✓		✓					Alu	33.895	32.200
	F25GES	2	432	EFI	18,4	56	25	E			✓	✓		opc.			Alu	35.211	33.450
	F25GEL	2	432	EFI	18,4	58	25	E			✓	✓		opc.			Alu	35.526	33.750
	F25GETL	2	432	EFI	18,4	64	25	E	✓		✓	✓		opc.			Alu	39.579	37.600
	F30BEHDL	3	747	EFI	22,1	102	25	E		✓		✓					Alu	37.884	35.990
	F30BETS	3	747	EFI	22,1	94	25	E	✓		✓	✓		✓			Alu	44.105	41.900
	F30BETL	3	747	EFI	22,1	98	25	E	✓		✓	✓		✓			Alu	44.421	42.200
	F40FEHDS	3	747	EFI	29,4	97	25	E		✓		✓		✓			Alu	44.421	42.200
	F40FEHDL	3	747	EFI	29,4	102	25	E		✓		✓		✓			Alu	45.211	42.950
	F40FEDL	3	747	EFI	29,4	102	25	E	✓		✓	✓		✓			Alu	45.211	42.950
	F40FETS	3	747	EFI	29,4	94	25	E	✓		✓	✓		✓			Alu	48.105	45.700
	F40FETL	3	747	EFI	29,4	98	25	E	✓		✓	✓		✓			Alu	48.411	45.990
akcija	F40HETL	4	996	EFI	29,4	110	25	E	✓		✓	✓		✓	✓		Alu	51.042	48.490
akcija	F40GETL	4	996	EFI	29,4	119	25	E	✓		✓	✓		✓	✓		Alu	59.463	56.490
	F50HETL	4	996	EFI	36,8	114	25	E	✓		✓	✓		✓	✓		Alu	57.368	54.500
	FT50JETL	4	996	EFI	36,8	125	25	E	✓		✓	✓		✓	✓		Alu-DT	58.937	55.990
	F60FETL	4	996	EFI	44,1	114	25	E	✓		✓	✓		✓	✓		Alu	65.474	62.200
	FT60GETL	4	996	EFI	44,1	125	25	E	✓		✓	✓		✓	✓		Alu-DT	67.895	64.500
	FT60GETX	4	996	EFI	44,1	127	25	E	✓		✓	✓		✓	✓		Alu-DT	68.158	64.750
	F70AETL	4	996	EFI	51,5	119	25	E	✓		✓	✓		✓	✓		Alu	73.579	69.900
	F70AETX	4	996	EFI	51,5	121	25	E	✓		✓	✓		✓	✓		Alu	73.579	69.900
	F80DETL	4	1.832	EFI	58,8	162	-	E	✓		✓	✓		✓	✓		Alu	77.579	73.700
	F80DETX	4	1.832	EFI	58,8	166	-	E	✓		✓	✓		✓	✓		Alu	78.053	74.150
	F100FETL	4	1.832	EFI	73,5	162	-	E	✓		✓	✓		✓	✓		Alu	81.684	77.600
	F100FETX	4	1.832	EFI	73,5	166	-	E	✓		✓	✓		✓	✓		Alu	84.105	79.900
	F115BETL	4	1.832	EFI	84,6	173	-	E	✓		✓	✓		✓	✓		Alu	86.947	82.600
	F115BETX	4	1.832	EFI	84,6	178	-	E	✓		✓	✓		✓	✓		Alu	88.947	84.500
*	FL115BETX	4	1.832	EFI	84,6	178	-	E	✓		✓	✓		✓	✓		Inox SDS	103.053	97.900
	F130AETL	4	1.832	EFI	95,6	174	-	E	✓		✓	✓		✓	✓		Alu	92.947	88.300
	F130AETX	4	1.832	EFI	95,6	178	-	E	✓		✓	✓		✓	✓		Alu	95.368	90.600
*	F150DETL	4	2.670	EFI	110,3	222	-	E	✓		✓	✓		✓	✓		Inox SDS	103.474	98.300
	FL150DETL	4	2.670	EFI	110,3	222	-	E	✓		✓	✓		✓	✓		Inox SDS	115.579	109.800
	F150DETX	4	2.670	EFI	110,3	227	-	E	✓		✓	✓		✓	✓		Inox SDS	105.158	99.900
*	FL150DETX	4	2.670	EFI	110,3	227	-	E	✓		✓	✓		✓	✓		Inox SDS	113.158	107.500
	F150GETL	4	2.785	EFI	110,3	226	-	E	✓		✓	✓		✓	✓		Inox SDS	123.684	117.500
	F150GETX	4	2.785	EFI	110,3	227	-	E	✓		✓	✓		✓	✓		Inox SDS	124.526	118.300
*	FL150GETX	4	2.785	EFI	110,3	227	-	E	✓		✓	✓		✓	✓		Inox SDS	124.526	118.300
	F175AETL	4	2.785	EFI	128,7	224	-	E	✓		✓	✓		✓	✓		Inox SDS	122.947	116.800
	F175AETX	4	2.785	EFI	128,7	225	-	E	✓		✓	✓		✓	✓		Inox SDS	125.053	118.800
	F175CETL	4	2.785	EFI	128,7	226	-	E	✓		✓	✓		✓	✓		Inox SDS	133.368	126.700
	F175CETX	4	2.785	EFI	128,7	227	-	E	✓		✓	✓		✓	✓		Inox SDS	134.211	127.500
*	FL175CETX	4	2.785	EFI	128,7	227	-	E	✓		✓	✓		✓	✓		Inox SDS	134.211	127.500
	F200FETL	4	2.785	EFI	147,1	226	-	E	✓		✓	✓		✓	✓		Inox SDS	133.368	126.700
	F200FETX	4	2.785	EFI	147,1	227	-	E	✓		✓	✓		✓	✓		Inox SDS	133.368	126.700
*	FL200FETX	4	2.785	EFI	147,1	227	-	E	✓		✓	✓		✓	✓		Inox SDS	137.474	130.600
	F200GETL	4	2.785	EFI	147,1	226	-	E	✓		✓	✓		✓	✓		Inox SDS	145.579	138.300
	F200GETX	4	2.785	EFI	147,1	227	-	E	✓		✓	✓		✓	✓		Inox SDS	147.684	140.300
*	FL200GETX	4	2.785	EFI	147,1	227	-	E	✓		✓	✓		✓	✓		Inox SDS	147.684	140.300
	F225BETX	V6	3.352	EFI	165,5	283	-	E	✓		✓	✓		✓	✓		Inox SDS	137.474	130.600

F200F i F200G opremljeni su V.C.T. (Variable Camshaft Timing)- sustavom varijabilnog zakretanja bregastih osovin